

BASWA Prime

2023 / 1



Product description and application areas

Organically bound, sound-transparent acoustic plaster for the base layer of BASWA acoustic systems.

Product Specifications

Article number	a002b: BASWA Prime in 50 liter bucket a002c: BASWA Prime in cardboard box
Material	Acoustic coating based on polymeric binders with mineral fillers
Grain size	0.5 – 1.0 mm
Consumption per m²	1.75 – 2.4 kg/m ²
Colour	grey-white
Weight / Content	a002b: Delivery weight gross (incl. bucket): approx. 14.0 kg Mixed approx. 19.0 kg net a002c: Delivery weight gross: approx. 13.1 kg Mixed approx. 19.0 kg net

Storage	Protect from frost, keep only in original packing Storage-/transport temperature between +5 °C and +30 °C Protect from direct sunlight Store in a dry place on pallets Can be stored up to 12 months under optimal conditions
----------------	--

Delivery

Delivery form	Bucket or cardboard box (350 mm x 350 mm x 300 mm)
----------------------	--

Delivery Information	Incorrect transport can lead to damage
-----------------------------	--

For further delivery information please contact BASWA acoustic AG, T +41 (0)41 914 02 22.

Material Preparation

1. Fill the required quantity of clean water (approx. 4.0 – 5.0 liters) into the bucket up to the mark.
2. Add binder concentrate and mix thoroughly with the water in the bucket (min.30 sec).
3. Add the bag of light filler and mix to a creamy mixture.

Note: Detailed instructions for preparing material in the bucket / box.

Application

1. Apply BASWA Prime with the stainless steel 3 mm x 3 mm (BASWA Basic system - 4 mm x 4 mm notched trowel also possible) or 6 mm x 6 mm (BASWA DTG system) notched trowel over the entire surface of the already glued and flat sanded surface and smoothen it to a flat, even surface (Size of the notched trowel depends on substrate and installation situation).
2. After sufficient and complete drying, sand the surface flat (Observe drying time and room conditions -> min. 24 hours / mm layer thickness).
3. Subsequently coat the surface, which has been ground flat, with BASWA acoustic plaster (BASWA Base / Fine / Top / Casual) in accordance with the latest BASWA application guidelines.

Legal notice

The above information, in particular the suggestions for the processing and use of our products, are based on our expertise and experience in the normal case, provided that the products have been stored and applied properly. Because of the different materials, surfaces and different working conditions, no guarantee of a work result or a liability, no matter what legal relationship, can be inferred from these notes or from a verbal consultation, unless it can be shown that we have acted with intent or gross negligence. Here, the user must prove that he has provided BASWA with all the information required for a proper and promising assessment by BASWA, on time and in full. The user must test the products for their suitability for the intended purpose. The product specifications are subject to change without notice. The protective rights of third parties must be observed. In addition, our respective terms and conditions of sale and delivery apply. The latest product data sheet, which can be requested from us, applies.